

RAPTOR RUNDOWN

December 3rd

Parent/Teacher Conference

Translators will be available upon request. Please notify your advisory if we need to arrange for these accommodations.

Thursday, December 6th – 4:00 to 5:30 pm

Friday, December 7th – 1:00 -6:00 pm

(EARLY DISMISSAL @ 11:45am

Buses will be available.)

Front Office Hours

**Monday, Tuesday,
Thursday, and Friday:**

7:45 am—4:30 pm


Wednesday:

7:45 am—2:30 pm

Phone: (303)524-6300

www.dsstpublicschools.org

DSST GVR MS will be participating this year in the Xcel Energy Program. During parent teacher conferences we will be providing Xcel energy kits that include the following:



AERATORS

You will need: pliers or adjustable wrench, cloth, rubber washer(s)

1. Remove old aerator from the faucet. Use a tool if needed.
2. Turn on water briefly to wash out faucet. Turn water off.
3. Screw on the new aerator, using the washer(s) provided and hand-tighten. For inside-threaded faucets: place both washers in the aerator (thinner washer first) and screw aerator into inside threads of faucet. For outside-threaded faucets: discard the thicker washer. With the thinner washer in top of aerator, screw aerator onto outside threads.
4. Turn on water. If aerator leaks, tighten by using wrench. Use cloth to protect the finish. Tighten until snug. Do not over-tighten.



LED BULBS

1. Use the LED bulbs in your kit to replace inefficient bulbs.

2. Before replacing a bulb, be sure the light switch is turned off and the bulb is not hot. Carefully unscrew the old bulb and dispose of it.
3. Screw the LED into the bulb socket. Do not over-tighten.



FILTER WHISTLE

Your furnace and air conditioner will run more efficiently when your furnace filter is clean. The whistle will remind you when the filter needs to be changed.

1. Begin with a new filter or remove the filter from your furnace. You will want to install the whistle on a clean filter.
2. Pull the whistle apart, so you have two pieces, the flat base and the hat. The filter will go in between the two parts of the whistle. The base must face the direction of the airflow and the hat clips on the opposite side.
3. Press the two parts of the whistle together, pushing through the filter until you hear the pieces click into place.
4. Install the filter in your furnace.



SHOWERHEAD

You will need: pliers or adjustable wrench, cloth, plumber's tape

1. Using pliers/wrench, remove old showerhead from the shower arm by turning to the left.
2. Clean shower arm threads, then turn on the water to wash out the pipe.
3. Turn off water. Apply plumber's tape to the threads for a tight seal.
4. Screw on the new showerhead and hand-tighten. Make no more than 1/4 turn with pliers/wrench.



TOILET LEAK DETECTOR TABLETS

1. Carefully take off tank lid. This should be done by an adult.
2. Drop one tablet into the tank water.
3. Wait 10 – 20 minutes.
4. If blue color appears in the bowl, you have a leak.

Important dates:

NOVEMBER 2018

- Parent teacher conference Thursday, December 6th from 4:00 to 5:30 pm
- Ceremony Award by invitation only, High Honors and Effort-Improvement
- Parent teacher conference 2nd day, Friday December 7th from 1:00
- DPS buses available

Useful Links

facebook.com/dsstgvrms

Uniforms:

http://thinkitgraphics.com/dsst_gvr/shop/home

www.dsstpublicschools.org

If your student is going to be absent, don't forget to call the attendance line at 303-524-6300 x 8029001

Front office: X 8023102

X 8023104